

## New Refined Fuel - READY TO ROLL



**CALL FOR DETAILS:  
(888) 681-3660 - Option 2**

**LOCATION: SACRAMENTO, CA**

Basic information	
<b>Stock Number</b>	<b>I0799 (Tank serial 15098, chassis vin HJ127514)</b>
Tank unit details	
<b>Tank Model, Size, &amp; Compartments</b>	Polar GT 4500 AEB6 T4
<b>Compartment Sizes</b>	800//1000//1200//1500
<b>MC Rating</b>	MC-406
<b>Cross section &amp; Profile</b>	Elliptical, bolster mount
<b>Emergency valves</b>	Betts EV46934ALT 3" X 3" 90*
<b>Pumps</b>	2 Blackmer TXD 2.5AVC, w/air piston relief valve
<b>Meters</b>	Liquid Controls M-7, with high capacity strainer/air eliminator, preset & optical vapor eliminator
<b>Registers</b>	LCR-II, electronic register, with in cab printer
<b>Hose reels, hoses, &amp; nozzles</b>	3 Hannay hose reels, all roadside pull, 2 in roadside open rack, vapor reel frame mounted behind rear tandem, with: * 75' of 1-1/4" Goodyear Redwing hose with 1-1/4" Scully nozzles with camlocks * 50' of 1-1/4" Goodyear Redwing hose with 2" camlock
<b>PTO'S</b>	2 Muncie Hot-shift air operated, controls in roadside open rack
<b>Controls Location</b>	2 OPW Civacon Civacontrol air control panels, in roadside open rack
<b>Dry Brakes or Manifold</b>	OPW Civacon Civaflo, dual air manifold system, curbside with product returns
<b>OverFill System</b>	Civacon, OPW-4100, 5 wire system, with out monitor & includes probe #1112-012
<b>Vapor Recovery</b>	Civacon
<b>Misc. Equipment</b>	* Fire extinguisher * Betts L.E.D. lighting * Chock block holder & chocks * Single rear ladder, center mounted * Open all aluminum rack 98" roadside * 1 aluminum cabinet curbside: 1-24" x 24" x 36" * 2 7" x approx. 20' hose tubes, 1 curbside & 1 roadside
Chassis details	
<b>Chassis Year, Make and Model</b>	2017 Kenworth T680
<b>Engine</b>	PACCAR MX-13, 455 hp@1700 rpm, 1650 lb/ft torque @ 1000 rpm, with engine brake
<b>Fuel type</b>	Diesel, 90 gallon polished aluminum, under cab, roadside
<b>Transmission</b>	FULLER FRO16210C 10-speed manual
<b>Front axle rating</b>	13,200 Meritor MFS13, 3.5" drop w/taperleaf springs
<b>Rear axle rating</b>	40,000 Meritor MT40-14X4 Amboid, w/KW AG380 air ride suspension
<b>GVWR</b>	53,200
<b>Misc.</b>	Alcoa LVL1 aluminum rims, qty 10